

AMR HORIZONTAL




Hydropneumatic tanks with bladder Booster sets

- Hydropneumatic tanks specially designed for booster sets
- Material: Steel
- Replaceable bladder according to EN 13831, suitable for drinking water
- Galvanized water connection (R 1")
- 4 feet
- Precharge valve
- Gas (precharge): Air
- External red epoxy powder coating
- Manufactured according to 2014/68/EU Directive
- 2 year warranty



Technical specifications

- | | |
|--------------------------|----------------|
| ▪ Volume: | 20 – 50 Liters |
| ▪ Bladder: | Replaceable |
| ▪ Max. service pressure: | 10 Bar |
| ▪ Test pressure: | 15 Bar |
| ▪ Precharge EXWORKS: | 1,5 Bar |
| ▪ Temperature max.: | 100°C |
| ▪ Temperature mín.: | -10°C |
| ▪ Water connection: | 1" G.M |



Weight (Kg)	Code	Model	Volume (Lts.)	Pressure (Bar)	ØD (mm)	L (mm)	H (mm)	water connection R
6	01020281	20 AMR-S	20	10	270	420	295	1"
12	01050281	50 AMR-S	50	10	360	620	390	1"
16	03080261	80 AMR-S	80	10	450	625	480	1"
18	03100211	100 AMR-S	100	10	450	750	480	1"