

AMR-PLUS HORIZONTAL



Hydropneumatic tanks with bladder Booster sets

- Hydropneumatic tanks specially designed for booster sets
- Material: Steel
- Replaceable bladder according to EN 13831, suitable for drinking water
- Brass water connection (R 1 1/2")
- Flange with threaded connection (R 1" GM)
- Precharge valve
- Gas (precharge): Nitrogen
- External blue epoxy powder coating RAL-5012, specially for outdoor
- Manufactured according to 2014/68/EU Directive
- 5 year warranty



Technical specifications

- | | |
|---|--------------------|
| ▪ Volume: | 150 – 1.000 Liters |
| ▪ Bladder: | Replaceable |
| ▪ Max. service pressure: | 10 Bar |
| ▪ Test pressure: | 15 Bar |
| ▪ Precharge EXWORKS: | 3 Bar |
| ▪ Temperature máx.: | 100°C |
| ▪ Temperature mín.: | -10°C |
| ▪ Bottom brass water connection: | R 1 1/2" G.M. |
| ▪ Coated flange with threaded connection: | R 1" G.M. |

Weight (Kg)	Code	Model	Volume (Lts.)	Pressure (Bar)	ØD (mm)	H (mm)	L (mm)	Water connection R
40	03150211	150 AMR-PLUS-H	150	10	485	655	1.070	1 1/2"
489	03220211	220 AMR-PLUS-H	200	10	485	655	1.320	1 1/2"
60	03350211	350 AMR-PLUS-H	300	10	485	655	1.810	1 1/2"
90	03500211	500 AMR-PLUS-H	500	10	600	780	1.930	1 1/2"
158	03700211	700 AMR-PLUS-H	700	10	700	880	2.100	1 1/2"
224	03900321	900 AMR-PLUS-H	900	10	800	1.000	2.070	1 1/2"
274	03910021	1000 AMR-PLUS-H	1.000	10	800	1.000	2.375	1 1/2"

