

AMR WITHOUT FEET





Hydropneumatic tanks with bladder Booster sets

- Hydropneumatic tanks specially designed for booster sets
- Material: Steel
- Replaceable bladder according to EN 13831, suitable for drinking water
- Galvanized water connection (R ¾" - R 1")
- Precharge valve
- Gas (precharge): Air
- External red epoxy powder coating
- Manufactured according to 2014/68/EU Directive
- 2 year warranty



Especificaciones técnicas

- | | |
|--------------------------|---------------|
| ▪ Volume: | 5 – 50 Liters |
| ▪ Bladder: | Replaceable |
| ▪ Max. service pressure: | 8-10 Bar |
| ▪ Test pressure: | 12-15 Bar |
| ▪ Precharge EXWORKS: | 1,5 Bar |
| ▪ Temperature max.: | 100°C |
| ▪ Temperature mín.: | -10°C |
| ▪ Water connection: | R ¾" - 1" G.M |



Weight (Kg)	Code	Model	Volume (Lts.)	Pressure (Bar)	ØD (mm)	H (mm)	Water connection R
2	01005013	5 AMR	5	10	200	245	¾"
2	01005014	5 AMR	5	10	200	245	1"
23,5	01008021	8 AMR	8	10	200	350	1"
4	01015021	15 AMR	15	10	270	320	1"
4,5	01020021	20 AMR	20	10	270	425	1"
9	01035021	35 AMR	35	10	360	485	1"
10	01050021	50 AMR	50	10	360	620	1"
4,5	01025051	24 AMR-E	24	8	350	390	¾"
4,5	01025061	24 AMR-E	24	8	350	390	1"