

CMF VERTICAL BOTTOM CONNECTION



Fixed membrane expansion vessels Cooling and heating closed systems

- Fixed membrane expansion vessel for cooling and heating systems.
- Material: Steel
- Non-replaceable membrane, according to EN 13831 (non potable)
- Water connection: R 1"
- Precharge valve
- Gas precharge: Air
- External red epoxy powder coating
- Manufactured according to 2014/68/EU Directive
- 2 year warranty



Technical specifications

- | | |
|--------------------------|--------------------|
| ▪ Volume: | 500 – 1.000 Liters |
| ▪ Membrane: | Non-replaceable |
| ▪ Max. service pressure: | 6 Bar |
| ▪ Test pressure: | 9 Bar |
| ▪ Precharge EXWORKS: | 1,5Bar |
| ▪ Temperature max.: | 100°C |
| ▪ Temperature min.: | -10°C |
| ▪ Water connection: | R1" G.M |



Weight (Kg)	Code	Model	Volume (Lts.)	Pressure (Bar)	ØD (mm)	H (mm)	Water connection R
63	04500351	500 CMF	500	6	750	1.445	1"
77	04600351	600 CMF	600	6	750	1.700	1"
95	04800351	800 CMF	800	6	750	2.155	1"
118	04101351	1000 CMF	1.000	6	750	2.555	1"