

## HMF HYDROCARBONS




### Hydropneumatic tanks with bladder Booster sets (Hydrocarbons)

- Hydropneumatic tanks for hydrocarbons
- Material: Steel
- Non-replaceable bladder, suitable for hydrocarbons
- Galvanized water connection
- Precharge valve
- Gas (precharge): Nitrogen
- External red epoxy powder coating
- Manufactured according to 2014/68/EU Directive
- 2 year warranty



#### Technical specifications

- |                                |                 |
|--------------------------------|-----------------|
| ▪ Volume:                      | 1 – 25 Liters   |
| ▪ Bladder:                     | Non replaceable |
| ▪ Max. service pressure:       | 3-8-10 Bar      |
| ▪ Test pressure:               | 4,5-12-15 Bar   |
| ▪ Precharge EXWORKS:           | 1,5 Bar         |
| ▪ Temperature max.:            | 100°C           |
| ▪ Temperature mín.:            | -10°C           |
| ▪ Galvanized water connection: | R 3/4"          |



Weight (Kg)	Code	Model	Volume (Lts.)	Pressure (Bar)	ØD (mm)	H (mm)	Water conncction R
1	06002621	1 HMF	1	3	226	82	¾"
1,5	06002631	2 HMF	2	3	230	130	¾"
2	06005631	5 HMF	5	10	200	250	¾"
2,5	06008631	8 HMF	8	10	200	340	¾"
3,2	06015631	15 HMF	15	10	270	320	¾"
4,2	06025631	25 HMF	25	8	320	430	¾"